

# BT070AECAHB352a\$

## 7.0" Color TFT-LCD video module.

### TFT LCD:

1. 7.0 inch TFT LCD panel **BT070AENNHBS\$**.
2. View angle (U/D/L/R): **35/55/70/70**
3. Resolution: **480\*(RGB)\*234 (pixels)**,  
**0.321 (H) x 0.370 (V)** mm dot pitch.
4. Brightness (cd/m<sup>2</sup>): **250cd/m<sup>2</sup>** Typical.
5. Contrast Ratio: **250:1**.
6. Active area: **154.08(H)\*86.58(V)** mm.
7. Panel Dimension: **164.9(W)\*100.0(H)\*5.0(D)**(typ.).

### Video Board:

1. Power Requirements: **12.0V DC±10%**.
2. Operating Temperature Range: **0~ +50°C**.
3. Storage Temperature Range: **-10~ +60°C**.
4. Dimension (W x H x T): **73.5\*54.6\*7.5 mm**.
5. Keyboard (optional): 5 Keys with OSD menu for image quality tuning supported.
6. Input Video: **CVBS\*1**.
7. Input impedance: **75Ω**.
8. Video system: **NTSC/PAL/SECAM auto detection**.



### Ordering Information:

Part NO.	Option(1) Bracket	Option(2) Host Cable	Option(3) Keyboard(with keyboard cable)
BT070AECAHB\$			
BT070AECAHB352\$	√	√	
BT070AECAHB352a\$	√	√	√
BT070AECAHB352b\$		√	√
BT070AECAHB352c\$		√	
BT070AECAHB352d\$	√		
BT070AECAHB352e\$	√		√
BT070AECAHB352f\$			√

### Dimension:

