

# PORTI-P340 – 3" Panel Printer



## General Features

- Compact Size  
110mm x 77.7mm x 48mm.
- Lightweight 300g.
- Silent direct thermal printing.
- High Speed (50mm/sec).
- High Resolution (203dpi, 8 dots/mm).
- UART or TTL Interface
- Low Power consumption.
- Easy paper loading (clamshell design)
- State of the art 2 dimensional barcode print technology.
- Easy maintenance with self diagnostics

## Technical Specification

Printing	Direct Thermal Printing
Paper Loading	Clamshell Design
Characters per line	64cpl
Character Size	Eng: 9 x 24 dots, 12 x 24 dots Kor: 16 x 24 dots, 24 x 24 dots
Dots per line	576 dots
Resolution	203dpi, 8 dots/mm
Print Width	3" (72mm, 576 dots)
Printing Speed	50mm/sec
Dimensions (W x D x H)	110mm x 77.7m x 48mm
Weight	300g (including paper roll)
Paper Supplied	80mm wide (40mm Ø)
Interface	UART or TTL
Input Power	9VDC @ 3.0A Max
Barcode Supported	1-Dimension: Code128, EAN 128, Code 39, UPC, EAN, KAN, JAN, CODABAR, I 2/5 2-Dimension: PDF417, QR Code, DATA Matrix
Receive Buffer Size	10k bytes
Print Head Life	50km
Relative Humidity	10 to 80% (non-condensing)
Operating temperature	-10°C to 40°C

## Standard Accessories

Roll of Paper,



Craft Data Limited

92 Broad Street, Chesham, Bucks, HP5 3ED

☎ 01494 778235 ☎ 01494 773645

✉ sales@craftdata.co.uk 🌐 www.craftdata.co.uk

