

PORTI-P60/PP60 – 2" Panel Printer



General Features

- Compact Size 76mm x 93mm x 62mm
- Lightweight (P60: 274g, PP60: 285g)
- Silent direct thermal printing.
- High Speed (50mm/sec).
- High Resolution (203dpi, 8 dots/mm).
- P60: UART or TTL Interfaces
PP60: UART & Parallel interfaces
- Low Power consumption.
- Easy paper loading (clamshell design)
- State of the art 2 dimensional barcode print technology.
- Easy maintenance with self diagnostics
- Supports both text and graphics

Technical Specification

Printing	Direct Thermal Printing
Paper Loading	Clamshell Design
Characters per line	42cpl
Character Size	Eng: 9 x 24 dots, 12 x 24 dots Kor: 16 x 24 dots, 24 dots x 24 dots
Dots per line	384dots
Resolution	203dpi, 8 dots/mm
Print Width	2" (48mm, 384 dots)
Printing Speed	50mm/sec
Dimensions (W x D x H)	76mm x 93mm x 62mm
Weight	P60: 274g PP60: 285g
Paper Supplied	57mm wide (60mm Ø)
Interface	P60: UART or TTL PP60: UART & Parallel
Receive Buffer Size	10K bytes
Input Power	9VDC @ 3.0A
Barcode Supported	1-Dimension: Code128, Code 39, EAN 128, UPC, EAN, KAN, JAN, CODABAR, I2/5 2-Dimension: PDF417, QR Code, DATA Matrix
Print Head Life	50km
Relative Humidity	10 to 80% (non-condensing)
Operating temperature	-10°C to 40°C

Standard Accessories

Roll of Paper,



Craft Data Limited
92 Broad Street, Chesham, Bucks, HP5 3ED
☎ 01494 778235 ☎ 01494 773645
✉ sales@craftdata.co.uk 🌐 www.craftdata.co.uk

