

PORTI-S30/S40 – 2" Portable Pocket Printer



General Features

- Pocket Size (76mm x 103mm x 34mm).
- Lightweight (226~264g).
- Silent direct thermal printing.
- High Speed (60mm/sec).
- High Resolution (203dpi, 8 dots/mm).
- UART or TTL plus IrDA Ver1.0 or Bluetooth Ver2.0 Interface options.
- Easy paper loading (clamshell design)
- State of the art 2 dimensional barcode print technology.
- Easy maintenance with self diagnostics
- Self Adhesive Label Printing Version (**S40**).

Technical Specification

Printing	Direct Thermal Printing
Paper Loading	Clamshell Design
Characters per line	40cpl
Character Size	ENG: 9 x 24 dots, 12 x 24 dots KOR: 16 x 24 dots, 24 x 24 dots
Dots per line	384 dots
Resolution	203dpi, 8 dots/mm
Print Width	2" (48mm, 384 dots)
Printing Speed	60mm/sec
Dimensions (W x D x H)	76mm x 103mm x 34mm
Weight	S30-226g (including battery pack + paper roll) S40-264g (including battery pack + paper roll)
Paper Supplied	57mm wide (S30 - 30mm Ø, S40 - 40mm Ø)
Interface	UART or TTL plus IrDA Ver1.0 or Bluetooth Ver2.0
Barcode Supported	1-Dimension: Code128, EAN128, Code 39, UPC, EAN, KAN, JAN, CODABAR, I 2/5 2-Dimension: PDF417, QR Code, DATA Matrix
Battery	Rechargeable 7.4VDC, 1200mAH (Li-ion)
Battery Charger	Input 100 to 250VAC, 50 to 60Hz, Output 8.4VDC/0.8A (4 hours for full charge – 1 hour continuous printing)
Print Head Life	50km
Relative Humidity	10 to 80% (non-condensing)
Operating temperature	-10°C to 50°C

Standard Accessories

Battery Charger
Serial interface cable
Roll of Paper
Leatherette carry case/belt pouch.

Optional Accessories

In-vehicle adaptor/charger



Craft Data Limited

92 Broad Street, Chesham, Bucks, HP5 3ED

☎ 01494 778235 ☎ 01494 773645

✉ sales@craftdata.co.uk 🌐 www.craftdata.co.uk

