

PORTI-WC40 – 4" Portable Pocket Printer with MSR



General Features

- Pocket Size (138.4mm x 88.5mm x 45.7mm).
- Lightweight (420g).
- Silent direct thermal printing.
- High Speed (50mm/sec).
- High Resolution (203dpi, 8 dots/mm).
- UART or TTL plus Bluetooth Ver2.0 Interfaces for maximum flexibility.
- Built-in MSR (tracks 2 & 3)
- Easy paper loading (clamshell design)
- State of the art 2 dimensional barcode print technology.
- Easy maintenance with self diagnostics
- Microsoft Windows CE, 98/ME/XP/2000 compatible.
- Self-Adhesive Label Printing Version

Technical Specification

| | |
|------------------------|--|
| Printing | Direct Thermal Printing |
| Paper Loading | Clamshell Design |
| Characters per line | 92cpl |
| Character Size | Eng: 9 x 24 dots, 12 x 24 dots Kor: 16 x 24 dots, 24 x 24 dots |
| Dots per line | 832 dots |
| Resolution | 203dpi, 8 dots/mm |
| Print Width | 4" (104mm, 832 dots) |
| Printing Speed | 50mm/sec |
| Dimensions (W x D x H) | 138.4mm x 88.5mm x 45.7mm |
| Weight | 420g (including battery pack) |
| Paper Supplied | 112mm wide (40mm Ø) Label Roll 112mm wide (40mm Ø) |
| Interface | UART plus Bluetooth Ver2.0 |
| Barcode Supported | 1-dimension: Code128, Code 39, EAN128, I2/5, UPC, EAN, KAN, JAN, CODABAR, 2-dimension: PDF417, QR Code, DATA Matrix |
| MSR | ISO/IEC 7810, ISO/IEC 7811 (2/3 Track) |
| Battery | Rechargeable 7.4VDC, 1.4A (Li-ion) |
| Battery Charger | Input 85 to 240VAC, 50 to 60Hz, Output 8.4VDC (4 hours for full charge – 1 hour continuous printing) |
| Print Head Life | 50km |
| Relative Humidity | 10 to 80% (non-condensing) |
| Operating temperature | -10°C to 50°C |

Standard Accessories

Battery Charger, Roll of Paper,
Serial interface cable.

Optional Accessories

In-Vehicle adaptor/charger



Craft Data Limited

92 Broad Street, Chesham, Bucks, HP5 3ED

☎ 01494 778235 ☎ 01494 773645

✉ sales@craftdata.co.uk 🌐 www.craftdata.co.uk

