

# PORTI-AP60 – 2" Panel Printer with Autocutter



## General Features

- Compact Size 107.2mm x 109.1mm x 90.6mm
- Lightweight 451g (inc. paper roll)
- Silent direct thermal printing.
- High Speed (50mm/sec).
- High Resolution (203dpi, 8 dots/mm).
- Serial RS-232C or RS-485, Parallel Interface options
- Low Power consumption.
- Easy paper loading (clamshell design)
- State of the art 2 dimensional barcode print technology.
- Easy maintenance with self diagnostics
- Supports both text and graphics
- Integrated Autocutter (full & partial cut)

## Technical Specification

Printing	Direct Thermal Printing
Paper Loading	Clamshell Design
Characters per line	42cpl
Character Size	9 x 24 dots, 12 x 24 dots
Dots per line	384dots
Resolution	203dpi, 8 dots/mm
Print Width	2" (48mm, 384 dots)
Printing Speed	50mm/sec
Dimensions (W x D x H)	107.2mm x 109.1mm x 90.6mm
Weight	451g (including paper roll)
Paper Supplied	57mm wide (60mm Ø)
Interface	Serial RS-232C or TTL
Receive Buffer Size	10K bytes
Input Power	Serial : 9VDC @ 3.0A Parallel : 12~24VDC @ 3.0A
Barcode Supported	PDF417 (2-dimensional), Code128, Code 39, UPC, EAN, KAN, JAN, CODABAR, I 2/5
Print Head Life	50km
Relative Humidity	10 to 80% (non-condensing)
Operating temperature	-10°C to 40°C

## Standard Accessories

Roll of Paper,



Craft Data Limited  
92 Broad Street, Chesham, Bucks, HP5 3ED  
☎ 01494 778235 ☎ 01494 773645  
✉ sales@craftdata.co.uk 🌐 www.craftdata.co.uk

