

PORTI-P30 – 2" Panel Printer



General Features

- Compact Size 77mm x 55mm x 30.3mm
- Lightweight 110g (inc. paper roll)
- Silent direct thermal printing.
- High Speed (50mm/sec).
- High Resolution (203dpi, 8 dots/mm).
- Serial RS-232C or TTL Interface
- Low Power consumption.
- Easy paper loading (clamshell design)
- State of the art 2 dimensional barcode print technology.
- Easy maintenance with self diagnostics
- Supports both text and graphics

Technical Specification

Printing	Direct Thermal Printing
Paper Loading	Clamshell Design
Characters per line	42cpl
Character Size	9 x 24 dots, 12 x 24 dots
Dots per line	384 dots
Resolution	203dpi, 8 dots/mm
Print Width	2" (48mm, 384 dots)
Printing Speed	50mm/sec
Dimensions (W x D x H)	77mm x 55mm x 30.3mm
Weight	110g (including paper roll)
Paper Supplied	57mm wide (30mm Ø)
Interface	Serial RS-232C or TTL
Receive Buffer Size	10K bytes
Input Power	5VDC @ 2.5A 9VDC @ 3.0A
Barcode Supported	PDF417 (2-dimensional), Code128, Code 39, UPC, EAN, KAN, JAN, CODABAR, I 2/5
Print Head Life	50km
Relative Humidity	10 to 80% (non-condensing)
Operating temperature	0°C to 40°C

Standard Accessories

Roll of Paper,



Craft Data Limited
92 Broad Street, Chesham, Bucks, HP5 3ED
☎ 01494 778235 📠 01494 773645
✉ sales@craftdata.co.uk 🌐 www.craftdata.co.uk

