

PORTI-SB50 – 2" Portable Pocket Printer



General Features

- Pocket Size (78mm x 131.5mm x 55mm).
- Lightweight (200g).
- Silent direct thermal printing.
- High Speed (50mm/sec).
- High Resolution (203dpi, 8 dots/mm).
- HPIR/IrDA and RS-232 or TTL Interfaces for maximum flexibility.
- Easy paper loading (clamshell design)
- State of the art 2 dimensional barcode print technology.
- Easy maintenance with self diagnostics
- Microsoft Windows 98/ME/XP/2000 compatible.

Technical Specification

Printing	Direct Thermal Printing
Paper Loading	Clamshell Design
Characters per line	42cpl
Character Size	Eng: 9 x 24 dots, 12 x 24 dots Kor: 16 x 24 dots, 24 x 24 dots
Dots per line	384 dots
Resolution	203dpi, 8 dots/mm
Print Width	2" (48mm, 384 dots)
Printing Speed	50mm/sec
Dimensions (W x D x H)	78mm x 131.5mm x 55mm
Weight	200g (not including dry cells)
Paper Supplied	57mm wide (50 mm Ø)
Interface	HPIR/IrDa and RS-232C or TTL
Barcode Supported	Code128, Code 39, UPC, EAN, CODABAR
Battery	Dry Cell (4xAA)
Battery Charger	Input 100 to 240VAC, 50 to 60Hz, Output 9VDC (800ma)
Print Head Life	50km
Relative Humidity	10 to 80% (non-condensing)
Operating temperature	0°C to 40°C

Standard Accessories

Battery Charger, Roll of Paper, Serial interface cable.



Craft Data Limited

92 Broad Street, Chesham, Bucks, HP5 3ED

☎ 01494 778235 📠 01494 773645

✉ sales@craftdata.co.uk 🌐 www.craftdata.co.uk

